



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	<ul style="list-style-type: none"> CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
--------------------	---

Physical

Number of rack unit	3U
Colour	Black
Depth	59 cm
Height	12.8 cm
Net weight	30.53 kg
Width	43.2 cm

Input

Network frequency	40...70 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	<ul style="list-style-type: none"> 50...150 V 40% load 80...150 V
Inputvolt_other	<ul style="list-style-type: none"> 220 V 240 V
Input voltage	230 V

Output

Rated power in W	1350 W
Maximum configurable power in W	1350 W
Harmonic distortion	Less than 2 %

Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvoltage_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	8 IEC 60320 C13
Bypass type	Built-in bypass
Output voltage	230 V

Conformance

Product certifications	CE EAC RCM VDE
Marking	CE Mark

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	450 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Li-Ion (Lithium-Ion)
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Liquid value	0
Battery voltage	48 V

Communications & Management

Free slots	0
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Package 1 Weight	46.86 kg
Package 1 Height	44.5 cm
Package 1 width	60 cm
Package 1 Length	85 cm
Number of Units in Package 3	6

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------