



TS-932PX-4G

| | |
|--|---|
| CPU | AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 quad-core 1.7GHz processor |
| CPU Architecture | 64-bit ARM |
| Floating Point Unit | Yes |
| Encryption Engine | Yes |
| System Memory | 4 GB SODIMM DDR4 (1 x 4 GB) |
| Maximum Memory | 16 GB (1 x 16 GB) |
| Memory Slot | 1 x SO-DIMM DDR4 |
| Flash Memory | 512 MB (Dual boot OS protection) |
| Drive Bay | 5x 3.5-inch+ 4 x 2.5-inch SATA 6Gb/s |
| Drive Compatibility | 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 2.5-inch bays: 2.5-inch solid state drives |
| Hot-swappable | Yes |
| 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | 2 |
| 10 Gigabit Ethernet Port | 2 x 10GbE SFP+ |
| Jumbo Frame | Yes |
| USB 3.2 Gen 1 port | 3 |
| Form Factor | Tower |
| LED Indicators | System Status, LAN, USB, HDD1~5, SSD1-4 |
| Buttons | Power, Reset, USB Copy |
| Dimensions (HxWxD) | 182.7 × 224.6 × 224.1 mm |
| Weight (Net) | 3.39 kg |

| | |
|--|--|
| Weight (Gross) | 4.99 kg |
| Operating temperature | 0 - 40 °C (32°F - 104°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | External, 120 W, AC 100 to 240 V |
| Fan | 1 x 140mm, 12VDC |
| Sound Level | 18.6 db(A) |
| System Warning | Voice prompts or Buzzer |
| Kensington Security Slot | Yes |
| Max. Number of Concurrent Connections (CIFS) | 1500 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.